

intimus[®] 602 HS

A MARTIN YALE BRAND



Operation

- On / off control automatic, via light barrier
- Cutout by autoreverse when overloaded and reversed

Equipment

- "Ready" indicator
- LEDs for paper jam, bin full or door open
- Dustproof enclosure - mounted on rollers for flexible use
- Large shelf - hinged to save space
- Large-volume catchbasket with changeable, environmentally acceptable PE bag

Technical features

- Electronics controlled by micro-controller
- Cutters made of solid, hardened special steel

Cutting mechanism is insensitive to

Paper clips	no
CDs / DVDs	no
3,5" floppy disks	no
Credit cards	yes
Passports	no
5 1/4" disks	no
Microfilms	yes
Identity cards	yes
Retaining clips	yes
Lam. paper/ overhead transparencies	yes
Paper and Colour cartons	yes

Performances intimus 602 HS

Particles	0,8 x 12 mm
Shredding capacity*	8 - 10 sheets
Security level DIN 32757-1	level 5
Working width	405 mm
Cutting speed	0,14 m/sec.
Catchbasket / Volume	130 l
Noise level	54 dB(A)
Power consumption/ Supply volt.	1,1/230 kW/volt
Dimensions W/ D/ H	66/43/102 cm
Weight	60 kg

* based on 70g/m² DIN A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply.
 Technical changes and colour variances reserved. 7/2005

