



Document Solutions

> PRINT

ECOSYS P2135d

MONOCHROME DESKTOP PRINTER
FOR A4 FORMAT

THE PROFESSIONAL DESKTOP PRINTER FOR MONO IN A4



For many businesses, the need for a fast, reliable and productive desktop laser printer is important for creating every day business documents. This compact, yet fast desktop monochrome laser printer provides users with up to 35 pages per minute, paper saving two-sided Duplex printing and connects easily to any PC with a standard USB interface. With its strong productivity and low total cost of ownership thanks to Kyocera's ECOSYS® long-life technology, the ECOSYS P2135 is the desktop printer you can count on.

- › Up to 35 pages per minute in A4
- › Fine 1,200 dpi printing quality
- › Standard duplex functionality for double-sided printing
- › Standard USB Connectivity
- › 250-sheet universal paper cassette
- › 50-sheet multi-purpose tray
- › Easy to read LED Operation Panel
- › Exceptionally low printing costs in its class



stands for ECOlogy, ECONomy and SYStem-printing. With long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly, and the drum units every 300,000 pages. The modular design concept allows you to add workflow-enhancing functions as required. Integrated system software provides long-term cross-network compatibility. Kyocera's long-life components cost you and the environment less.

PRESCRIBE IIc

With the Kyocera page design and control language PRESCRIBE IIc, even complex graphics, logos and forms (multipart forms) can be created independently on the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

GENERAL

Technology: Kyocera ECOSYS Laser Printer

Operating systems: All current Windows operating systems, Mac OS X Version 10.2 or higher, UNIX, LINUX as well as other operating systems on request

Engine speed: Up to 35 pages per minute in A4

Resolution: Fast 1,200 dpi, Fine 1,200 dpi (half speed)

Warm-up time: Approx. 15 seconds or less from power on

Time to first page: Approx. 6 seconds or less

Dimensions (W x D x H): 375 mm x 393 mm x 250 mm

Weight: Approx. 12 kg (main unit)

Power source: 220/240 V, 50/60 Hz

Power consumption:

Printing: 535 W

Stand-by: 7.1 W

Sleep: 2.6 W

Safety standards:

GS, TÜV, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

CPU: PowerPC 405F5/360 MHz

Memory: 32MB RAM, can be increased to 544MB (single DIMM slot as an option)

Standard interface: USB 2.0 (Hi-Speed), KUIO interface slot

PAPER HANDLING

All paper capacities quoted are based on 80gsm paper, thickness of 0.11mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: 50-sheet multi-purpose tray; 60-220 g/m²; A4, A5, A6, B5, Letter, Legal, Custom (70 x 148 – 215.9 x 356 mm), Folio, Oficio2

250-sheet universal paper cassette, 60-120 g/m²; A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 mm – 215.9 x 297 mm), Folio, Oficio2

Max. paper capacity incl. options: 800 sheets A4

Duplex unit: Double-sided printing standard supports: 60-105g/m²; A4, A5, B5, Letter, Legal, Custom (140 x 210 - 215.9 x 297mm)

Output capacity: 250 sheets face-down

PRINT FUNCTIONS

Controller language: PRESCRIBE IIc

Emulations: PCL6/PCL5e incl. PjL, KPD L 3 (PostScript 3 compatible) with automatic emulation switching (AES), Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630

Fonts/Barcodes: 80 outline fonts accessible in all emulations, 1 bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode PDF-417

The KYOCERA NetViewer

The KYOCERA NetViewer enables complete monitoring and control of all ECOSYS printers and digital Kyocera multifunction units from any Windows® PC and thus provides ideal network administration. It also supports the standardised SNMP protocol.

Status Monitor and Command Centre

The Status Monitor shows the current printers condition and gives direct access to the Command Centre for the modification of settings that are not contained in the drivers (e.g. network settings, adjustment of sleep mode or blocking of the control panel).

USB Host Interface for USB Flash Memory

PDF files can be printed directly from a USB Flash Memory (e.g. USB stick) via the USB host interface. Documents are selected directly via the printer's control panel. No computer is required.

OPTIONS

PF-100 Paper feeder (max. 2 units):

Max. 250 sheets; 60-120 g/m²; A4, A5, B5, Letter, Legal, Custom (148 x 210 mm – 215.9 x 297 mm)

Max. 2 x PF-100 can be attached for a total of 800 sheet input

Memory Upgrade:

DIMM-256B: 256MB

DIMM-512B: 512MB

1 slot available for memory upgrade

CompactFlash* card:

1 slot (up to 4 GB) for printing forms, fonts, logos, macro storage

Optional interface:

IB-23 Fast Ethernet: 10/100 Base-TX

CONSUMABLES

TK-174 Toner-Kit: Microfine toner for 7,200 pages A4, at 5% coverage, in accordance with ISO/IEC 19752
Capacity of starter toner is 2,300 pages A4, at 5% coverage, in accordance with ISO/IEC 19752

MK-174 Maintenance Kit: Installed at 100,000 pages



KYOCERA Document Solutions Australia
Ph: 13 KYOCERA (596 2372)
www.kyoceradocumentsolutions.com.au

KYOCERA Document Solutions New Zealand*
Ph: 0508 KYOCERA (596 2372)
www.kyoceradocumentsolutions.co.nz

* KYOCERA Document Solutions New Zealand is the trading name of the New Zealand branch of KYOCERA Document Solutions Australia Pty Ltd a corporation incorporated in Australia.

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.