



PRODUCTS | Multifunction Colour Laser



**NEW!**

## LEXMARK X954DE

Power up your office and increase productivity with the Lexmark X954de, featuring high-performance A3 colour functionality, flexible features, easy-to-use workflow solutions, advanced security and 2GB RAM.

» [Support](#)

OVERVIEW

SUPPLIES AND  
OPTIONS

TECH SPECS

|                         |  |
|-------------------------|--|
| <b>Print Technology</b> | Colour LED   |
| <b>UNSPSC Code</b>      | 43212110   |
| <b>Display</b>          | Lexmark e-Task 10.2-inch (25.9 cm) colour touch screen with audible and tactile feedback         |
| <b>Scanner Type</b>     | Flatbed scanner with ADF   |
| <b>ADF Scan</b>         | RADF (reversing Duplex)  |
| <b>Function</b>         | Colour Copying<br>Colour Faxing<br>Colour Printing<br>Colour Scanning<br>Colour Network Scanning |

**Print Speed (A4, mono): Up to** 55 ppm

**Print Speed (A4, mono) Duplex: Up to** 55 spm

**Print Speed (A4, colour): Up to** 50 ppm

**Print Speed (A4, colour) Duplex: Up to** 50 spm

**Print Speed (Letter, mono): Up to** 55 ppm

**Print Speed (Letter, mono) Duplex: Up to** 55 spm  
to

**Print Speed (Letter, Colour): Up to** 50 ppm



**Print Speed (Letter, Colour) Duplex: Up to** 50 spm

**Time to First Page (Black) As fast as** 5.0 seconds

**Time to First Page (Colour) as fast as** 7.2 seconds

**Copy Speed (A4, Black): Up to** 55 cpm

**Copy Speed (A4 mono) Duplex: Up to** 55 spm

**Copy Speed (A4, Colour): Up to** 50 cpm

**Copy Speed (Letter mono): Up to** 55 cpm

**Copy Speed (Letter mono) Duplex: Up to** 55 spm

**Copy Speed (Letter colour): Up to** 50 cpm

**Time to First Copy (Black) As fast as** 6.4 seconds

**Time to First Copy (Colour) as fast as** 9.9 seconds

**Print Resolution, Black** 1200 x 1200 dpi  
2400 Image Quality

**Print Resolution, Colour** 1200 x 1200 dpi  
2400 Image Quality

**Processor Speed** 1.2 GHz

**Memory, standard** 2048 MB

**Expandable Memory Options** No

**Memory, maximum** 2048 MB

**Hard Disk** as standard

**Apple Macintosh Operating Systems Supported** Apple Mac OS X

**Microsoft Windows Operating Systems Supported**

- Microsoft Windows XP
- Microsoft Windows Server 2003
- Microsoft Windows XP x64
- Microsoft Windows Server 2003 running Terminal Services
- Microsoft Windows Server 2003 x64
- Microsoft Windows Server 2003 x64 running Terminal Services
- Microsoft Windows Vista
- Microsoft Windows Vista x64
- Microsoft Windows Server 2008
- Microsoft Windows Server 2008 x64
- Microsoft Windows Server 2008 running Terminal Services
- Microsoft Windows Server 2008 x64 running Terminal Services
- Microsoft Windows 7
- Microsoft Windows 7 x64
- Microsoft Windows Server 2008 R2
- Microsoft Windows Server 2008 R2 running Terminal Services

|   |   |
|---|---|
| <b>Citrix MetaFrame</b>                       | Microsoft Windows Server 2003 running Terminal Services with Citrix Presentation Server 3.0, 4.0, 4.5<br>Microsoft Windows Server 2003 and 2003 X64 Edition with Citrix XenApp 5.0<br>Microsoft Windows Server 2008 and 2008 X64 Edition with Citrix XenApp 5.0           |
| <b>Linux Operating Systems Supported</b>      | Debian GNU/Linux 5.0<br>SUSE Linux Enterprise Server 10, 11<br>SUSE Linux Enterprise Desktop 10, 11<br>openSUSE 11.0, 11.1<br>Red Hat Enterprise Linux WS 4.0, 5.0<br>Red Flag Linux Desktop 6.0<br>Linpus Linux Desktop 9.6<br>Ubuntu 9.04, 9.10, 10.04<br>Fedora 12, 13 |
| <b>Novell Operating Systems Supported</b>     | Novell NetWare 6.5 Open Enterprise Server<br>Novell NetWare 5.1 (SP 6+), 6.0 (SP 3+) with Novell Distributed Print Services (NDPS)<br>Novell Open Enterprise Server on SUSE Linux Enterprise Server   |
| <b>UNIX Operating Systems Supported</b>       | Sun Solaris SPARC 8, 9, 10<br>Sun Solaris x86 10<br>HP-UX 11.11, 11.23, 11.31<br>IBM AIX 5.2, 5.3, 6.1  |
| <b>Paper Handling Standard</b>                | 500-Sheet Output Bin<br>Integrated Duplex<br>100-Sheet Multipurpose Feeder<br>520-Sheet Input Tray  |
| <b>Paper Input Capacity, Standard: Up to</b>  | 620 pages 75 gsm bond   |
| <b>Paper Input Capacity, Maximum: Up to</b>   | 5140 pages 75 gsm bond  |
| <b>Paper Output Capacity, Standard: Up to</b> | 500 pages 75 gsm bond   |
| <b>Paper Output Capacity, Maximum: Up to</b>  | 3750 pages 75 gsm bond  |
| <b>ADF Paper Input Capacity : Up to</b>       | 110 pages 75 gsm bond   |
| <b>Finishing Option</b>                       | Yes   |
| <b>ADF Paper Output Capacity : Up to</b>      | 110 pages 75 gsm bond   |
| <b>Envelope Capacity</b>                      | 10  |
| <b>Paper Handling Optional</b>                | 2,000-Sheet High Capacity Feeder<br>3,500-Sheet Finisher<br>3 x 520-Sheet Drawer Stand<br>Booklet Finisher<br>2,520-Sheet Tandem Tray Module<br>520-Sheet Drawer Stand  |
| <b>Number of Paper Inputs, Standard</b>       | 2   |
| <b>Number of Paper Inputs, Maximum</b>        | 6   |
| <b>Duplex (2-sided) Printing</b>              | Integrated Duplex   |
| <b>Media Types Supported</b>                  | Card Stock<br>Envelopes<br>Glossy paper<br>Labels   |

|                                     |   |
|-------------------------------------|---|
|                                     | Plain Paper<br>Transparencies<br>Refer to the Card Stock & Label<br>Guide   |
| <b>Media Sizes Supported</b>        | 10 Envelope<br>7 3/4 Envelope<br>A3<br>A4<br>A5<br>C5 Envelope<br>DL Envelope<br>Executive<br>Folio<br>JIS-B4<br>JIS-B5<br>Ledger<br>Legal<br>Letter<br>Statement<br>Universal<br>Super Tabloid (305 x 457 mm)<br>Oficio<br>A6                            |
| <b>Standard Ports</b>               | USB 2.0 Specification Hi-Speed<br>Certified (Type B)<br>Front USB 2.0 Specification Hi-Speed<br>Certified port (Type A)<br>Rear USB 2.0 Specification Hi-Speed<br>Certified port (Type A)<br>Ethernet 10/100/1000 BaseTX (RJ-<br>45)                      |
| <b>Optional Network Ports</b>       | External MarkNet™ N7020e Gigabit<br>Ethernet<br>Internal MarkNet™ N8120 Gigabit<br>Ethernet<br>Internal MarkNet™ N8130 Fiber Fast<br>Ethernet<br>Internal MarkNet™ N8250<br>802.11b/g/n Wireless  |
| <b>Optional Local Ports</b>         | Internal RS-232C serial<br>Parallel 1284-B Interface Card   |
| <b>Network Printing Methods</b>     | LPR/LPD<br>Direct IP (Port 9100)<br>HTTP<br>NDPS/NEPS (Novell Distributed Print<br>Services, Novell Netware Enterprise<br>Print Services)<br>Enhanced IP (Port 9400)<br>FTP, TFTP<br>IPP 1.1 (Internet Printing Protocol)<br>ThinPrint .print integration |
| <b>Network Protocol Support</b>     | TCP/IP IPv4<br>AppleTalk™<br>TCP/IP IPv6<br>TCP<br>UDP  |
| <b>Network Management Protocols</b> | HTTP<br>HTTPs (SSL*/TLS)<br>SNMPv3<br>WINS<br>IGMP<br>BOOTP, RARP<br>APIPA (AutoIP)<br>DHCP<br>ICMP<br>DNS<br>SNMPv2c<br>Bonjour<br>DDNS<br>mDNS<br>ARP<br>NTP<br>Telnet  |

|   |   |
|---|---|
|   | Finger  |
|   | *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit.  |
| <b>Network Security</b>                       | SNMPv3<br>802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS<br>IPSec  |
| <b>Fonts and Symbol Sets</b>                  | 3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide<br>158 scalable PostScript fonts<br>2 PCL bitmap fonts<br>39 scalable PPDS fonts<br>5 PPDS bitmap fonts<br>84 scalable PCL fonts<br>OCR-A, OCR-B scalable PCL 5e fonts |
| <b>Printer Languages (Standard)</b>           | For more information, refer to the Technical Reference.<br>PCL 5c Emulation<br>PCL 6 Emulation<br>PPDS<br>PostScript 3 Emulation<br>xHTML<br>PDF 1.6<br>Direct Image<br>Microsoft XPS (XML Paper Specification)                 |
| <b>Printable Area (metric)</b>                | 4.2 mm of the top, bottom, right and left edges (within)  |
| <b>Printable Area</b>                         | 0.167 inches of the top, bottom, right and left edges (within)  |
| <b>Reduce / Enlarge Range</b>                 | 25 - 400 %  |
| <b>Scan Area, Maximum</b>                     | 11.69 x 17 inches   |
| <b>Scan Area, Maximum (mm)</b>                | 297 x 432 mm  |
| <b>Modem Speed</b>                            | 33.6 Kbps   |
| <b>Packaged Size (in. - H x W x D)</b>        | 34.25 x 33.39 x 30.28 in.   |
| <b>Size (in. - H x W x D)</b>                 | 30.01 x 25.20 x 26.97 in.   |
| <b>Weight (kg)</b>                            | 116.0 kg  |
| <b>Weight (lb.)</b>                           | 255.8 lbs.  |
| <b>Packaged Size (mm - H x W x D)</b>         | 870 x 848 x 769 mm  |
| <b>Packaged Weight (kg)</b>                   | 125.0 kg  |
| <b>Packaged Weight (lb.)</b>                  | 275.6 lbs.  |
| <b>Size (mm - H x W x D)</b>                  | 762 x 640 x 685 mm  |
| <b>Size, Trays Extended (in. - H x W x D)</b> | 43.21 x 25.20 x 43.63 in.   |
| <b>Size, Trays Extended (mm - H x W x D)</b>  | 1098 x 640 x 1108 mm  |
| <b>Noise Level, Idle</b>                      | 24 dBA  |
| <b>Print Noise Level, Operating</b>           | 53 dBA  |

**Duplex Print Noise Level, Operating** 55 dBA

**Scanner Noise Level, Operating** 54 dBA

**Copier Noise Level, Operating** 55 dBA

**Product Certifications** Energy Star, CAN/CSA-C22.2 60950-1-07, ICES-003 Class A, BSMI Class A, CNS 13438 and 14336, VCCI Class A, FCC Class A, UL 60950-1, EN/IEC 60320-1, NOM-019-SCFI-1998, CB IEC 60950-1, EN 60950-1, EN/IEC 61000-3, EN 55022 Class A, EN 55024, GS (TÜV), SAT, SABS, ZIK, KPSIM, Bel GISS, GOST-R 'Cpt' Mark, N Mark, IRAM, CS, TÜV Rh, ACMA A-tick mark Class A, AS/NZS 60950-1, CCC Class A, GB4943, CISPIR 22 Class A, MIC Mark, EK-K60950, PSB-SS 337

**Product Guarantee** 1-Year Onsite Service, Next Business Day

**Recommended Monthly Page Volume** 5000 - 33000 Pages

**Maximum Monthly Duty Cycle: Up to** 250000 pages per month

**Duty Cycle Notes** "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

**Specified Operating Environment** Altitude: 0 - 2500 Meters (8,200 Feet)  
Temperature: 10 to 32°C (50 to 90° F)  
Humidity: 15 to 85% Relative Humidity

**Cartridge(s) Shipping with Product** 11,000\*-page Colour (CMY) Starter Toner Cartridges  
16,000\*-page Black Starter Toner Cartridge

**Supplies Yield** Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798.  
22,000\*-page Colour (CMY) Toner Cartridges  
32,000\*-page Black Toner Cartridge

**Energy Star Typical Electricity Consumption (TEC)** 9.462 kilowatt-hours per week

Available from: Allteq Pty Ltd - <http://www.allteq.com.au>

Copyright © 2010 Lexmark International, UK. All rights reserved.

Registered in England & Wales No. 2567373 Registered Office: Westhorpe House, Westhorpe, Marlow, Buckinghamshire SL7 3RQ.