



Fujitsu fi-6400
A3 Document
Scanners
FJ3077



The fi-6400 is the perfect scanning solution for small and medium sized companies who are looking to introduce a centralised document capture solution. Larger corporations seeking added flexibility from their scanning infrastructure could utilise the affordable fi-6400 for applications where decreasing scan requirements are needed across multiple locations, when there is a need for a higher throughput scanner to cover peak times or simply as a back-up system.

The fi-6400 minimises operator interference through automated functionality to provide uninterrupted performance when processing large batches of documents. The fi-6400 can scan at speeds of 100 pages per minute (ppm) or when double sided 200 images per minute (ipm) at 300 dpi in A4 landscape mode (85ppm/170ipm in A4 portrait mode). When higher resolutions are needed operators can select up to 600 optical dpi.

Main features: 100ppm (200ipm), 500p ADF, A3, True Duplex, USB2, 1 year warranty NBD OS covering up to 40,000 pages/day.

Fujitsu fi-6400

A3 Document Scanners

fi-6400 Specifications	
ADF (Doc. Feeder)	Yes
ADF Scan Area - Max.	297x420 mm
ADF Scan Area - Min.	52x74 mm
Duplex or Simplex	True Duplex
ADF Speed (ppm)	100
ADF Capacity (pages)	500
ADF Speed Duplex (ipm)	260
ADF Paper Path	U
Paper Weight	20 to 209 gsm (A4) or 41 to 209 gsm for other sizes
Duty Cycle	★★★★★
Colour Modes	B&W, Greyscale, Colour
Scanning Technology	CCD x 2
Interface	USB2
Resolution (dpi, optical)	600
File Formats	Text Searchable PDF, TIFF, JPEG, BMP
Supported OS	WINDOWS XP, VISTA, Win 7, Win 8 (32/64), Server 2008, Server 2012
Software Standards	TWAIN, ISIS (included)
Imaging Features	Automatic colour detection, Automatic page size detection, De-Skew, Automatic orientation, Upper lower separation, Multi-image, Blank page skip, Error diffusion, Dither, Dropout colour (R, G, B, None, White, Specified, Saturation), Image emphasis, Simplif
In the Box	PaperStream IP Driver (TWAIN & ISIS™), 2D Barcode for PaperStream, Software Operation Panel, Error Recovery Guide, PaperStream Capture, Scanner Central Admin tools
Electrical	Input: 100-240 VAC, 50/60 Hz. Power consumption:
Light Source	LED
Dimensions	460x430x310 mm
PC Configuration	Minimum: 1GB RAM, USB2. Recommended: 4GB RAM, USB2
Weight	58.25
Operating Environment	15°C to 35°C, 20-80%RH
Warranty	12 months parts & labour warranty