


RJ-2000 Series


2 Inch Receipt & Label Mobile Printers



Compact. Rugged. Connected.

Fast, compact, rugged and ready to connect to virtually any device. RJ-2000 series raises the bar in mobile printing performance, ruggedness and operating system compatibility.

- Fast. Prints at 152mm per second
- **Rugged.** IP54 certified, 2.5m drop tested, and tumble tested for long-term durability
- Versatile. Compatible with Android[™], iOS[®], and Windows[®] and available with dual wireless radio for Bluetooth[®] or WiFi support
- Advanced. First in 2" class to be Apple
 AirPrint® compatible and new REMOTE
 UPDATE feature to automatically update printer
 settings while in the field and actively in use











Transportation





Pest Management



Field Services



Mobile Professional



Public Safety

Technical Specifications for the RJ-2000 series

Model	RJ-2030	RJ-2050	RJ-2140	RJ-2150
Print Technology	Direct Thermal			
Print Resolution	203 dpi			
Maximum Print Speed	6 ips (152 mm/sec)			
Type of Brother Media Supported	Receipt, Label, and Tag (Labels and tags require a black mark) Receipt, Label, Tag Label			
User Interface	1 LED; 3 double function buttons, Monocrhome LCD 2.4"/320x120 dot with back light			
Dimension (WxHxD)	122 mm W x 57 mm H x 100 mm L 150 mm W x 73 mm H x 100 mm L			nm H x 100 mm L
Weight	355g without battery 465g with battery		435g without battery 545g with battery	
Print Width (Max)	54 mm			
Print Length (Min/Max)	12.7 mm; 1 m			
Roll Diameter (Max)	40mm (1.57")		60mm (2.36")	
Roll Width	Fixed Wall 55mm(Label), 58mm(Receipt) Must remove insert for wider width		Adjustable 25mm to 58mm	
Memory	32MB RAM; 32MB Flash (12MB Available)			
Label Editing Software	BarTender Ultra Lite Edition ¹			
USB Interface	USB Ver. 2.0 (full speed), mini B. No USB Host			
Bluetooth	Bluetooth	02.1+EDR	No	Bluetooth2.1+EDR
Bluetooth MFI	No	Yes	No	Yes
WLAN	N/A Wireless LAN IEEE802.11b/g/n (Infrastructure mode and Adhoc mode: [b/g/n] / Wireless direct mode:[g/n])			
WLAN Security	AdHoc Mode: Open system (None/WEP) Infrastructure Mode: Open system (None/WEP64/WEP128), Common key authentication (WEP), N/A WPA/WPA2-PSK (TKIP+AES), LEAP (CKIP), EAP-FAST (TKIP/AES), PEAP (TKIP/AES) *3, EAP-TLS (TKIP/AES), EAP-TTLS (TKIP/AES) Wireless Direct Mode: WPA2-PSK (AES)			
Drop Protection	2.5m Multiple drop (under controlled test environment)			
Sealing Certification	IP54 without case			
Operating T emperatures	Operate: -10° to 50°C (with charge: 0° to 40° C)			
Supported Printer Driver	Microsoft®, Windows® Vista®, Windows® 7 / Windows® 8 Windows® 8.1 / Windows® 10			
SDK	Android™ 4.0.3 or later; iOS® 6 and above; Windows® Mobile 5 and 6			
Supported Command Language	Raster, ESC/P, P-Touch Template, ZPLII emulation, CPCL emulation			
Barcode Symbologies	CODE39; ITF(I-2/5); EAN-13; EAN-8; UPC-A; UPC-E; CODABAR; CODE128; GS1-128(UCC/EAN-128); RSS symbols CODE93; POSTNET; UPC/EAN EXTENSION; MSI; QR Code (model 1, model 2, micro QR); PDF417 (Standard, Truncate, MicroPDF417); Data Matrix(ECC200 Square, ECC200 Rectangular); MaxiCode; Aztec			
Internal Fonts and Sizes	<esc p="">; Bitmap font: Gothic, Letter Gothic Bold, Helsinki 3 size<16, 24, 32dot>; Outline font: Gothic, Letter Gothic Bold, Helsinki Max: 400dot; <p-touch® template=""></p-touch®></esc>			
Power (Battery / Charger)	Rechargeable Li-ion battery: 7.2VDC; AC adapter (15 V) only for charging (50/60Hz); Cigarette car adapter or Wired type (12 VDC) only for charging; Drop in Battery Charger (PA-BC-002): Interlocking, expandable and horizontal mountable (up to 4 units, requires (PA-AD-600) AC adapter).			
Battery Life	4300 x (50mmx25mm) labels			
Package Contents	Printer, Belt Clip, Li-ion battery			
Warranty	12 Months Return To Base			

Accessories

 Optional accessories include extra batteries, shoulder strap, DC vehicle adapter, AC charger, battery charger and more.









www.brother.com.au 1300 885 989 corporatesales@brother.com.au